

Service Bulletin





GE-20-117

Transmission Shift Fork Cap Screws and Nuts - 2-85, 2-88, 2-105 and 2-110 Tractors

11-16-84

1 of 2




Fig. 1 - Flange Lock-Type Cap Screws and Nuts

SERVICE INFORMATION

Improved method of retaining transmission shift fork to rails was incorporated in 2-88 and 2-110 tractors at approximate tractor serial no. 303 141-000.

New reusable flange lock-type cap screws and nuts (Fig. 1) eliminate use of internal and external tooth lock washers and gives better locking capability.

RECOMMENDATION

During transmission overhaul on all 2-85, 2-88, 2-105 and 2-110 tractors, purchase and install the following (new) flange lock-type cap screws and nuts in place of superseded parts.

NOTE: Torque cap screws and nuts to 22 to 24 ft-1bs.

PARTS REPLACEMENT OR REPAIR AT COMPANY EXPENSE IS NOT AUTHORIZED UNLESS SUCH POLICY IS STATED.



Service Bulletin



GE-20-117

2 of 2

2-85 & 2-105

Superseded			New .			
Qty.	Part No.	Description	Qty.	Part No.	Description	
4	908 465	Cap Screw, 5/16-24 x 7/8	4	30-341 7743	Cap Screw, Flange Lock 5/16-24 x 7/8	
1	908 466	Cap Screw 5/16-24 x 1	. 1	30-341 8391	Cap Screw, Flange Lock 5/16-24 x 1	
2	908 467	Cap Screw, 5/16-24 x 1-1/4	2	30-341 8405	Cap Screw, Flange Lock 5/16-24 x 1-1/4	
6	920 155	Lock Washer, Internal Tooth - 5/16				
1	920 123	Lock Washer, External Tooth - 5/16				

2-88 & 2-110

	Superse	eded	New					
Qty.	Part No.	Description	Qty.	Part No.	Description	- 4		
4	908 465	Cap Screw, 5/16-24 x 7/8	4	30-341 7743	Cap Screw, Flange 5/16-24 x 7/8	Lock		
2	915 001 920 155	Nut, 5/16-24 Lock Washer, Internal	2	30-341 7751	Nut, Flange Lock,	5/16-24		
٠	920 133	Tooth - 5/16						

Service Department
430 1274