

AGRICULTURAL



FEBRUARY

PRESENTING

THE NEW 1957 SUPER 66, 77 AND 88 TRACTORS

Great tractors are being made greater at Oliver. The Super 66, 77 and 88 tractors are being further refined to give better service. Attractive appearance and real durability are combined here to produce customer satisfaction.

Outlined below are the improvements contained in the 1957 Models of the Super 66, 77 and 88.

ENGINE

- * Hardened exhaust valve inserts in HC models to provide longer life.
- * New pleated paper lubrication oil filter element with high capacity and effective filtration.

 One model for all Diesels One model for all HC models.
- * 1000 watt coolant heater is available to ease cold weather starting. Coolant temperature can be raised 40° in one hour.
- * New baffle type muffler of aluminized steel improves appearance and sound.
- * Heavier oil filter base for more rigid attachment and better oil sealing.
- * New tachourmeter conveniently located indicating engine RPM and hours. Has an easy to read dial and is now standard equipment.

ELECTRICAL SYSTEM:

- * Solenoid starter on diesels is controlled by the switch key.
- * Magnetic starter on HC models is controlled by the switch key.
- * All HC models now have 12-volt electrical systems, built around a 70 ampere hour battery.
- * Diesel models have two 6-volt 130 ampere hour batteries on Super 77 and 88, 115 ampere hour on Super 66, which boost starter RPM.
- * All models are now being equipped with dry batteries so that you have fresh batteries for delivery to your customer.

"PRODUCT KNOWLEDGE FIRST - SALES NEXT"



OLIVER



OLIVER

Page 2

GENERAL

- * External easy to reach grease fitting for lubricating the clutch release bearing. Now standard equipment.
- * Front frame is more heavily reinforced with added ribs and thickened flanges.
- * New three-point "Hydra-Hitch" fits the Fleetline and Supers. High lifting capacity is provided by the 4" Hydra-Lectric cylinder. Included in the Hydra-Hitch packages is a 4-position mounting step to add to operator convenience.
- * A new heavier drawbar (3" \times 7/8") on Super 77 and 88 will more than support today's heavy implements. The drawbar being wider and heat-treated gives longer life in swinging operation.
- * Power adjusted wheels are available for Super 66, 77 and 88. This adjustable wheel can be used with either the light or heavy cast wheels. Adjustment is made by loosening three jack screws and setting the lock stop, then applying tractor power to shift wheels as desired.
- * New full view battery door makes batteries easily serviced and accessible.

Since all tractors shipped from Charles City after January 1, 1957, have red wheels you should check specification number to be certain the tractor is a 1957 Model. The 1957 specification numbers for the Super 66 start at 26-0001, Super 77 at 27-0001 and Super 88 at 28-0001.

The new Super 66, 77 and 88 tractors have been designed to give years of excellent service. The added color on the wheels and the embossed "OLIVER" on the wheel guards add to the attractiveness of these tractors.

WHGardner:ds 2-25-57